







Roller Levers

Type	Roller			Catalog Number
	Material	Dia.	Width	
 Non-Adj. Cast Lever 0.75" Radius	Metal	0.75"	0.27"	802T-W9A
 Non-Adj. Cast Lever 1.5" Radius Roller on Front	Nylon	0.75"	0.28"	802T-W1
	Nylon	0.75"	1"	802T-W1H
	Dual Nylon	0.75"	1" each	802T-W1HH
	Steel	0.75"	0.25"	802T-W1A
	Steel	0.75"	0.75"	802T-W1N
	Ball Bearing	0.75"	0.23"	802T-W1B
	Beryllium Copper (Nonsparking)	0.75"	0.28"	802T-W1J
	Nylon	0.75"	0.75"	802T-W1L
 Non-Adj. Cast Lever 1.5" Radius Roller on Rear	Nylon	0.75"	0.28"	802T-W1E
	Nylon	0.75"	1"	802T-W1D
	Nylon	1.5"	0.28"	802T-W1G
	Steel	0.75"	0.25"	802T-W1F
	Steel	0.75"	0.75"	802T-W1C
	Nylon	0.75"	0.75"	802T-W1M
		Nylon	0.75"	0.28"
 Non-Adj. Steel Lever 2.0" Radius Roller on Front	Nylon	0.75"	1"	802T-W20D
	Steel	0.75"	0.25"	802T-W20A
	Steel	0.75"	0.75"	802T-W20B
	Ball Bearing	0.75"	0.23"	802T-W20C
	Beryllium Copper	0.75"	0.28"	802T-W20E
 Non-Adj. Steel Lever 2.0" Radius Roller on Rear	Nylon	0.75"	0.28"	802T-W20J
	Nylon	0.75"	1"	802T-W20K
	Steel	0.75"	0.25"	802T-W20L
	Steel	0.75"	0.75"	802T-W20M
	Ball Bearing	0.75"	0.23"	802T-W20N
	Beryllium Copper	0.75"	0.28"	802T-W20P
 Non-Adj. Steel Lever 2 1/8" Radius Roller on Front	Nylon	0.75"	0.75"	802T-W18
	Nylon	0.75"	1"	802T-W18A
 Non-Adj. Steel Lever 2.5" Radius Roller on Front	Nylon	0.75"	0.28"	802T-W25
	Nylon	0.75"	1"	802T-W25D
	Steel	0.75"	0.25"	802T-W25A
	Steel	0.75"	0.75"	802T-W25B
	Ball Bearing	0.75"	0.23"	802T-W25C
	Beryllium Copper	0.75"	0.28"	802T-W25E
 Non-Adj. Steel Lever 2.5" Radius Roller on Rear	Nylon	0.75"	0.28"	802T-W25J
	Nylon	0.75"	1"	802T-W25K
	Steel	0.75"	0.25"	802T-W25L
	Steel	0.75"	0.75"	802T-W25M
	Ball Bearing	0.75"	0.23"	802T-W25N
	Beryllium Copper	0.75"	0.28"	802T-W25P

Type	Roller			Catalog Number	
	Material	Dia.	Width		
 Non-Adj. Steel Lever 3.0" Radius Roller on Front	Nylon	0.75"	0.28"	802T-W30	
	Nylon	0.75"	1"	802T-W30D	
	Steel	0.75"	0.25"	802T-W30A	
	Steel	0.75"	0.75"	802T-W30B	
	Ball Bearing	0.75"	0.23"	802T-W30C	
	Beryllium Copper	0.75"	0.28"	802T-W30E	
 Non-Adj. Steel Lever 3.0" Radius Roller on Rear	Nylon	0.75"	0.28"	802T-W30J	
	Nylon	0.75"	1"	802T-W30K	
	Steel	0.75"	0.25"	802T-W30L	
	Steel	0.75"	0.75"	802T-W30M	
	Ball Bearing	0.75"	0.23"	802T-W30N	
	Beryllium Copper	0.75"	0.28"	802T-W30P	
 Adjustable Lever 1.19" to 3" Radius	Nylon	0.75"	0.28"	802T-W2	
	Nylon	0.75"	1"	802T-W2D	
	Nylon	1.5"	0.28"	802T-W2A	
	Steel	0.75"	0.25"	802T-W2B	
	Ball Bearing	0.75"	0.23"	802T-W2C	
	Steel	1.4"	0.27"	802T-W2E	
	Rubber	1.5"	0.5"	802T-W2R	
		Beryllium Copper	0.75"	0.28"	802T-NX94
		Nylon	0.75"	0.28"	802T-W17
	Nylon	1.5"	0.28"	802T-W17A	
 Adjustable Lever 1.19" to 4" Radius	Nylon; L.H. Roller on Front; R.H. Roller on Back	0.75"	0.28"	802T-W4	
	Steel; L.H. Roller on Front; R.H. Roller on Back	0.75"	0.25"	802T-W4B	
	Nylon; Both Rollers on Front	0.75"	0.28"	802T-W4A	
	Nylon; Both Rollers on Rear	0.75"	0.28"	802T-NX115	
 Fork Lever 1.5" Radius	Nylon; Both Rollers on Front	0.75"	1"	802T-W4F	
	Steel; Both Rollers on Front	0.75"	0.25"	802T-W4C	
	Nylon; L.H. Roller on Back; R.H. Roller on Front	0.75"	0.28"	802T-W4D	
	Nylon R.H. Adj.	0.75"	0.28"	802T-W6	
	Steel R.H. Adj.	0.75"	0.25"	802T-W6A	
 Micrometer Adjustment Lever 1.5" Radius	Ball Bearing R.H. Adj.	0.75"	0.23"	802T-W6B	
	Nylon L.H. Adj.	0.75"	0.28"	802T-W6C	
	Steel L.H. Adj.	0.75"	0.25"	802T-W6D	
	Ball Bearing L.H. Adj.	0.75"	0.23"	802T-W6E	
	Nylon R.H. Adj.	0.75"	1"	802T-W6F	

① The micrometer adjustment roller lever is designed especially for installations where the position of the roller is a critical factor. This lever has a pivoted roller which can be turned laterally. After clamping the lever to the switch shaft, the position of the roller can be precisely adjusted through an arc of 7.5° on either side of the center or straight-line position.