

ENTRANCE CAPS

PC 5690

Clamp on service entrance caps permit a weather resistant entrance for type SE cable on rigid, IMC or EMT for pulling service drop conductors. They are assembled with an electrical grade Phenolic insulator with multiple holes.



CAT. NO.	UPC	SIZE	STD	MSTR	WT/STD
EC50	40005	1/2"	25		6.21#
EC75	40010	3/4"	25		7.18#
EC100	40015	1"	25		8.97#
EC125	40020	1-1/4"	10		4.89#
EC150	40025	1-1/2"	10		7.56#
EC200	40030	2"	5		6.09#
EC250	40035	2-1/2"	1		3.83#
EC300	40040	3"	1		5.43#
EC350	40045	3-1/2"	1		6.47#
EC400	40050	4"	1		6.78#

FEATURES:

- UL Listed
- Die Cast Copper Free Aluminum
- Phenolic Insulator
- Clamp On Style
- Weather Resistant

ENTRANCE ELLS (SLB)

PC 5700

Service Entrance Ells are used with threaded rigid conduit or IMC for providing access to the interior of a conduit system for pulling, splicing, inspection and maintenance.



CAT. NO.	UPC	SIZE	STD	MSTR	WT/STD
SLB50	40100	1/2"	10	100	2.01#
SLB75	40105	3/4"	10	100	2.60#
SLB100	40110	1"	5	50	2.15#
SLB125	40115	1-1/4"	5	50	3.76#
SLB150	40120	1-1/2"	2	20	1.83#
SLB200	40125	2"	2	10	2.69#

FEATURES:

- UL Listed
- Die Cast Copper Free Aluminum
- Assembled with Fiber Gasket & Aluminum Cover
- Weather Resistant

PULLING ELLS

PC 5710

Pulling Ells are used to connect two lengths of threaded rigid conduit or IMC to form a 90° bend and provide access for wire pulling.



CAT. NO.	UPC	SIZE	STD	MSTR	WT/STD
PE1	40130	1/2"	10	100	1.89#
PE2	40135	3/4"	10	100	2.69#
PE3	40140	1"	5	25	2.50#

FEATURES:

- UL Listed
- Die Cast
- High Strength Zinc Alloy
- Removable Aluminum Cover & Neoprene Gasket