

LED replacement lamps

RS Cans

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
RS Cans																		
	E26	10	95853	LED10RS4/827E26P	120	12	5.88	700		2700	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment	
				95854	LED10RS4/830E26P	120	12	5.88	700		3000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
	GU24			95855	LED10RS4/827GUP	120	12	5.88	700		2700	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
				95856	LED10RS4/830GUP	120	12	5.88	700		3000	80	65W	50,000	Yes	★	Damp	4" Can, Pigtail Attachment
	E26			85153	LED10RS6/827E26P	120	12	7.5	700		2700	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
				85160	LED10RS6/830E26P	120	12	7.5	700		3000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
	GU24			95851	LED10RS6/827GUP	120	12	7.5	700		2700	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
				95852	LED10RS6/830GUP	120	12	7.5	700		3000	80	65W	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
	E26	13		70120	LED13RS6/827E26P	120	12	7.5	1000		2700	80	90w	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
				70122	LED13RS6/830E26P	120	12	7.5	1000		3000	80	90w	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
	GU24			70124	LED13RS6/827GUP	120	12	7.5	1000		2700	80	90w	50,000	Yes	★	Damp	6" Can, Pigtail Attachment
				70127	LED13RS6/830GUP	120	12	7.5	1000		3000	80	90w	50,000	Yes	★	Damp	6" Can, Pigtail Attachment

LED Tubes

Integrated and Refit

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	DLC	UL	#Location Rating	Additional Information	
Integrated 4ft LED Tubes (operates on Instant Start or Program Start Ballast)																	
T8	G13	18	31550	LED18ET8/4/830		25	48	2200	3000K	80+		50,000	Yes	Yes	Damp	Dimmability Requires PRS Ballast	
	G13	18	93133	LED18ET8/4/835		25	48	2200	3500K	80+		50,000	Yes	Yes	Damp	Dimmability Requires PRS Ballast	
	G13	18	93135	LED18ET8/4/840		25	48	2200	4000K	80+		50,000	Yes	Yes	Damp	Dimmability Requires PRS Ballast	
	G13	18	93140	LED18ET8/4/850		25	48	2200	5000K	80+		50,000	Yes	Yes	Damp	Dimmability Requires PRS Ballast	
Integrated 3ft LED Tubes (operates on Instant Start or Program Start Ballast)																	
G13	12	31554	LED12ET8/3/830		25	36	1400	3000K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
	12	26544	LED12ET8/3/835		25	36	1400	3500K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
	12	26625	LED12ET8/3/840		25	36	1400	4000K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
	12	26627	LED12ET8/3/850		25	36	1400	5000K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
Integrated 2ft LED Tubes (operates on Instant Start or Program Start Ballast)																	
G13	9	31557	LED9ET8/2/830		25	24	1100	3000K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
	9	26635	LED9ET8/2/835		25	24	1100	3500K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
	9	26648	LED9ET8/2/840		25	24	1100	4000K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
	9	26676	LED9ET8/2/850		25	24	1100	5000K	80+			50,000	-	Yes	Damp	Dimmability Requires PRS Ballast	
Refit 4 ft LED Tubes (operates with Remote Driver)																	
T8	G13	16	88138	LED18T8/4/850/BT		25	48	2300	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	94381	LED21T8/4/835		10	48	2100	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	94382	LED21T8/4/840		10	48	2100	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	94383	LED21T8/4/850		10	48	2200	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	26059	LED21T8/4/865		10	48	2200	6500K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	62428	LED21T8/G/4/835		10	48	2200	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	62485	LED21T8/G/4/840		10	48	2200	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	18	62487	LED21T8/G/4/850		10	48	2300	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
Refit 3 ft LED Tubes (Operates with Remote Driver)																	
T8	G13	16	82343	LED18T8/3/835		10	36	1800	3500K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	
	G13	16	82345	LED18T8/3/840		10	36	1800	4000K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	
	G13	16	82346	LED18T8/3/850		10	36	1800	5000K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	
Refit 2 ft LED Tubes (Operates with Remote Driver)																	
T8	G13	8	92997	LED9T8/2/865		20	24	900	6500K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	
	G13	8	65706	LED9T8/2/835		20	24	900	3500K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	8	65707	LED9T8/2/840		20	24	900	4000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
	G13	8	65711	LED9T8/2/850		20	24	900	5000K	80+		50,000	Yes	Yes	Damp	Requires Driver / Dimming Driver	
Refit LED U-Tubes (Operates with Remote Driver)																	
T8	G13	12	28084	LED14T8/U/835		15	U - 1 5/8	1700	3500K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	
	G13	12	28164	LED14T8/U/840		15	U - 1 5/8	1700	4000K	80+		50,000	-	Yes	Damp	Requires Driver / Dimming Driver	

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
 ** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.
 2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

Get more information at
GELighting.com/ThinkLED